
5610/5611/5611T/5665 Temperature Probes, Reference Thermistor Probes

Highlights

Lab-grade thermistors probes for accurate work across a narrow temperature range

- Temperature probes with short-term accuracy to ± 0.01 °C; one-year drift $< \pm 0.01$ °C
- Accredited NVLAP calibration optional
- Flexible PTFE and silicone coated fast-response models
- Rugged polished stainless steel sheaths

Hundreds of thousands of thermistors and temperature probes are sold every year, but only a few have the stability necessary for use as high-accuracy thermometry standards. If you're looking for economical lab-grade thermistor probes for accurate work across a narrow temperature range, Fluke Calibration Secondary Reference Series thermistor probes are the best you can buy.

Description

These temperature probes are available in a variety of sheath materials appropriate for your specific application. In addition to our metal-sheathed temperature probes, we offer flexible PTFE encapsulated and silicone coated thermistors that have smaller tips and can measure those places where even a metal-sheathed thermistor can't reach.

PTFE encapsulated thermistor

The 5611T is an especially versatile PTFE coated thermistor probe. With a PTFE encapsulated tip that is just 3 mm (0.12 in) in diameter and a PTFE coating that makes it impervious to most liquids, the PTFE Probe is handy for measuring in a wide variety of applications, including bio-pharmaceuticals. It's even immersible to nearly 20 feet and flexible enough that you could roll it up into a ball in your hand if you wanted to!

The 5611T's thermistor bead is encapsulated in a Mylar sleeve that is encapsulated inside a PTFE sleeve. The PTFE sleeve is then melted around the PTFE-insulated cable, forming a moisture-proof seal.

Stainless steel sheathed thermistors

Our stainless steel metal-sheath probes include our 5610-6 and 5610-9 immersion probes, as well as our 5665 fully immersible probe. These probes are great for measuring in air, liquid or soil.

Silicone coated thermistor

With a diameter at the tip of just 1.5 mm (0.06 in), the 5611A's tip has the smallest diameter of any of our secondary reference thermistors and can fit nearly anywhere. Its faster response time, flexible sheath, and silicone coating make the 5611A great for use in many applications. However, applications involving silicone oil could damage the thermistor and should be avoided.

Higher performance

All Fluke Calibration secondary reference thermistors have small diameters and very small sensing elements, which means they require far less immersion than a PRT to avoid errors caused by stem effect. Self heating is usually negligible, giving them an advantage when taking measurements in air. Their small size also improves response time, allowing measurements to be taken more quickly.

If your application involves frequent handling, you'll be especially interested to know thermistors are less susceptible to mechanical shock than PRTs. The bottom line may be better accuracy in fieldwork.

Additionally, higher base resistance and larger resistance coefficients make it easier to achieve precision readings with thermistors, so better resolution and accuracy are possible for a lower cost. All of these thermistors have a negative temperature coefficient of resistance (NTC).

Readouts

These probes come in a complete assembly ready for use, and each works well with the uncertainties of our thermometer readouts: the 1504 Tweener, the 1523 and 1524 Handheld Thermometers, the 1529 Chub-E4, the 1560 Black Stack, and the

Thermometer, but they are most portable when used with a handheld reference thermometer.

Calibrated accuracy

What's more, the Secondary Reference Series Thermistors are accurate to $\pm 0.01\text{ }^{\circ}\text{C}$ and cover the temperature range of $0\text{ }^{\circ}\text{C}$ to $100\text{ }^{\circ}\text{C}$. They come with a NIST-traceable calibration and a resistance-versus-temperature table printed in $0.1\text{ }^{\circ}\text{C}$ increments that can be interpolated to $0.0001\text{ }^{\circ}\text{C}$. NVLAP accredited calibrations as single thermistors or as systems combined with their readouts, are also available.

No other sensors can match the accuracy and price combination of these high-accuracy thermistor probes. Try one and you'll agree.

Specifications

Specifications	
Resistance	Nominal $10,000\ \Omega$ at $25\text{ }^{\circ}\text{C}$
Range	$0\text{ }^{\circ}\text{C}$ to $100\text{ }^{\circ}\text{C}$
Calibration	R vs. T table with $0.1\text{ }^{\circ}\text{C}$ increments, interpolation equation furnished
Calibration Uncertainty	Table and equation are accurate to $\pm 0.01\text{ }^{\circ}\text{C}$ Optional accredited† calibration uncertainties $\pm 0.006\text{ }^{\circ}\text{C}$
Drift	Better than $\pm 0.01\text{ }^{\circ}\text{C}$ per year ($k=3$)
Repeatability	Better than $\pm 0.005\text{ }^{\circ}\text{C}$
Termination	Specify when ordering.
†NVLAP Lab Code 200348-0	

Models and Accessories

Model Name	Description
5610-6-X	Thermistor Probe, 3.2 mm dia x 152.4 mm (0.125 in x 6 in), $0\text{ }^{\circ}\text{C}$ to $100\text{ }^{\circ}\text{C}$ (Calibration traceable to NIST standards included) <i>X = termination. Specify "A" (INFO-CON for 914X), "B" (bare wire), "D" (5-pin DIN for Tweener Thermometers), "G" (gold pins), "I" (INFO-CON for 1521 or 1522), "J" (banana plugs), "L" (mini spade lugs), "M" (mini banana plugs), "P" (INFO-CON for 1523 or 1524), or "S" (spade lugs).</i>
5610-9-X	Thermistor Probe, 3.2 mm dia x 228.6 mm (0.125 in x 9 in), $0\text{ }^{\circ}\text{C}$ to $100\text{ }^{\circ}\text{C}$ (Calibration traceable to NIST standards included) <i>X = termination. Specify "A" (INFO-CON for 914X), "B" (bare wire), "D" (5-pin DIN for Tweener Thermometers), "G" (gold pins), "I" (INFO-CON for 1521 or 1522), "J" (banana plugs), "L" (mini spade lugs), "M" (mini banana plugs), "P" (INFO-CON for 1523 or 1524), or "S" (spade lugs).</i>
5611A-11X	Silicone-Bead Probe, 1.5 mm dia x 25.4 mm (0.06 in x 1 in), $0\text{ }^{\circ}\text{C}$ to $100\text{ }^{\circ}\text{C}$ (Calibration traceable to NIST standards included) <i>X = termination. Specify "A" (INFO-CON for 914X), "B" (bare wire), "D" (5-pin DIN for Tweener Thermometers), "G" (gold pins), "I" (INFO-CON for 1521 or 1522), "J" (banana plugs), "L" (mini spade lugs), "M" (mini banana plugs), "P" (INFO-CON for 1523 or 1524), or "S" (spade lugs).</i>
5611T-X	Teflon Probe, 3.2 mm dia x 28 mm (0.12 in x 1.1 in), $0\text{ }^{\circ}\text{C}$ to $100\text{ }^{\circ}\text{C}$ (Calibration traceable to NIST standards included) <i>X = termination. Specify "A" (INFO-CON for 914X), "B" (bare wire), "D" (5-pin DIN for Tweener Thermometers), "G" (gold pins), "I" (INFO-CON for 1521 or 1522), "J" (banana plugs), "L" (mini spade lugs), "M" (mini banana plugs), "P" (INFO-CON for 1523 or 1524), or "S" (spade lugs).</i>

5665-X	Miniature Immersion Probe, 3.2 mm dia x 76.3 mm (0.125 in x 3 in), 0 °C to 100 °C (Calibration traceable to NIST standards included) X = termination. Specify "A" (INFO-CON for 914X), "B" (bare wire), "D" (5-pin DIN for Tweener Thermometers), "G" (gold pins), "I" (INFO-CON for 1521 or 1522), "J" (banana plugs), "L" (mini spade lugs), "M" (mini banana plugs), "P" (INFO-CON for 1523 or 1524), or "S" (spade lugs).
--------	--

Accessories common to all models:

Accessory	Description
2601	Probe Carrying Case, Plastic (for probes up to 228 mm [9 in] in length)
2609	Probe Carrying Case, Plastic (for probes 635 mm [25 in] in length)





©1995-2014 Fluke Corporation [in](#) [RSS](#)
