







Temperature measurement and calibration

Tools for industrial instrumentation and calibration technicians

FLUKE®

Calibration

Industrial temperature calibration selection guide

Look inside for:

Field metrology wells

Infrared calibrators

Handheld and field dry-wells

Micro-baths

Environmental monitoring

Thermometer readouts

Reference sensors



Selection guide

	Field metrology wells			NEW! Precision infrared calibrators		Handheld dry-wells	
	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	2015) 2015)	2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		0	*	
Model	9142/9142P page 4	9143/9143P page 4	9144/9144P page 4	4180 page 6	4181 page 6	9100S page 8	9102S page 8
Range	-25 °C to 150 °C 4-20 mA	33 °C to 350 °C 4-20 mA	50 °C to 660 °C 4-20 mA	−15 °C to 120 °C	35 °C to 500 °C	35 °C to 375 °C	−10 °C to 122 °C
Best accuracy	± 0.2 °C	± 0.2 °C	± 0.35 °C	± 0.35 °C	± 0.35 °C	± 0.25 °C	± 0.25 ℃
Applications	•	•	•	+	*		

	Field dry-wells		Sensors				
		í B	9			O	
Model	9009 page 9	9103 page 10	9140 page 10	9141 page 10	9150 page 10	PRT page 15	Thermistor page 15
Range(s)	−15 °C to 350 °C	−25 °C to 140 °C	35 ℃ to 350 ℃	50 °C to 650 °C	150 °C to 1200 °C	−200 °C to 670 °C	0 °C to 100 °C
Best accuracy	± 0.2 ℃	± 0.25 °C	± 0.5 °C	± 0.5 °C	± 5 °C	See pages 14-15	See pages 14-15
Applications	■ *	#	■ *	*	thermocouples	◆■ *	◆■ *

	Micro baths			Thermometer readouts and environmental monitoring				
							23.74± 43.1	
Model	6102 page 11	7102 page 11	7103 page 11	1551A/1552A page 13	1523/1524 page 13	1529 page 14	1620A page 12	
Range	35 °C to 200 °C	−5 °C to 125 °C	-30 °C to 125 °C	−200 °C to 300 °C	−200 °C to 2315 °C	−200 °C to 962 °C	15 °C to 35 °C 20 %RH to 70 %RH	
Best accuracy	± 0.25 °C	± 0.25 °C	± 0.25 °C	± 0.05 ℃	± 0.015 °C	± 0.006 °C	± 0.25 °C ± 2 %RH	
Channels	n/a	n/a	n/a	n/a	1 or 2	4	2	
Applications	*	*	*	■ *	*	*	*	

Handheld dry-wells



Temperature sensor calibration is easy with a handheld dry-well.

Ordering information

9100S Handheld Dry-Well

9300 Rugged Carrying Case, 9100 9102S Handheld Dry-Well, comes with your

choice of two 3102 inserts

9308 Hard Carrying Case, 9102/9132

9320A Battery Pack, 115V (9102S run

time: 4 hrs)

3102-1 Insert, AL 1/16 in (1.6 mm) **3102-2** Insert, AL 1/8 in (3.2 mm)

3102-3 Insert, AL 3/16 in (4.8 mm)

3102-4 Insert, AL 1/4 in (6.4 mm) (Standard) **3102-6** Insert, AL 3/8 in (9.5 mm) (Standard)

3102-7 Insert, AL 7/16 in (11.1 mm) (Standard)

3102-8 Insert, AL 5/32 in (4 mm) (Standard)

2514 Dry-well interface cable to Fluke 754


Insert. Specify "A", "B", "D"

Fluke Calibration 9100S and 9102S Handheld **Dry-Well Temperature Calibrators**

- A temperature source that you can take anywhere
- Fast and easy calibrations of temperature sensors
- 9100S model weighs only 2 lbs, 3 oz (1 kilogram)
- Temperature ranges from -10 °C to 375 °C
- Stability during calibrations to \pm 0.05 °C
- Direct interface to the Fluke 754 Documenting Process Calibrator


Each unit includes RS-232 interface, instrument control software and a NIST-traceable calibration.

Recommended accessories: carrying case, additional inserts, reference temperature sensor and indicator, battery pack



Easily connect a Fluke 754 to a dry-well for a fully automated temperature calibration that includes the temperature transmitter and temperature sensor.

9100 fixed-block options





FLUKE ®

Calibration

Training

Calibration and metrology training from Fluke Calibration can help you and your staff become more knowledgeable in a wide variety of disciplines. Instructors are experts who work in electrical, temperature, pressure and flow calibration, and who really want to help you learn the foundation and techniques of metrology that you can put to immediate use in your workplace. Fluke Calibration offers introductory, intermediate, and advanced level courses in a variety of formats to meet your needs.

Training Seminars in American Fork, Utah

Get real training from real experts that lays out the basics and builds up to more advanced material for more advanced learners.

- · Principles of Temperature Metrology
- Advanced Topics in Temperature Metrology
- Infrared Temperature Metrology
- Temperature Calibration Product Training

Service

Some of the best service and lowest uncertainties are available in our primary and secondary calibration laboratories located in the US and Europe. We offer NVLAP accredited calibration services in the US and UKAS accredited calibration services are available in Europe. Don't forget to pay a visit to our calibration laboratory when you come for training.





16

Fluke Calibration. Precision, performance, confidence.™

Electrical RF Temperature Pressure Flow Software

