



# TL1000-MC4

## Test Leads

### Safety Information

A **Warning** identifies hazardous conditions and procedures that are dangerous to the user. A **Caution** identifies conditions and procedures that can cause damage to the Product or the equipment under test.

#### Warning

To prevent possible electrical shock, fire, or personal injury:

- Read all safety information before you use the Product.
- Use the Product only as specified, or the protection supplied by the Product can be compromised.
- Carefully read all instructions.
- Do not use the Product if it is altered or damaged.
- Comply with local and national safety codes. Use personal protective equipment (approved rubber gloves, face protection, and flame-resistant clothes) to prevent shock and arc blast injury where hazardous live conductors are exposed.
- Use Product-approved measurement category (CAT), voltage, and amperage rated accessories (probes, test leads, and adapters) for all measurements.

---

PN 5339320 (English) August 2022  
©2022 Fluke Corporation. All rights reserved. Specifications are subject to change without notice. All Product names are trademarks of their respective companies.

- Do not touch voltages >30 V ac rms, 42 V ac peak, or 60 V dc.
- Do not use the Product around explosive gas, vapor, or in damp or wet environments.
- Do not exceed the Measurement Category (CAT) rating of the lowest rated individual component of a Product, probe, or accessory.
- Do not use test leads if they are damaged. Examine the test leads for damaged insulation, exposed metal, or if the wear indicator (if present) shows. Check test lead continuity.
- Do not disconnect the test leads when under load.

## Symbols

The table below is a list of the symbols that can be used on the Product or in this document.

| Symbol                                                                              | Description                                                                                                                                                                                                                                                                                                                                                      |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|    | Consult user documentation.                                                                                                                                                                                                                                                                                                                                      |
|    | WARNING. RISK OF DANGER.                                                                                                                                                                                                                                                                                                                                         |
|    | WARNING. HAZARDOUS VOLTAGE. Risk of electric shock.                                                                                                                                                                                                                                                                                                              |
|  | Double insulated                                                                                                                                                                                                                                                                                                                                                 |
|  | Conforms to European Union directives.                                                                                                                                                                                                                                                                                                                           |
| <b>CAT III</b>                                                                      | Measurement Category III is applicable to test and measuring circuits connected to the distribution part of the building's low-voltage MAINS installation.                                                                                                                                                                                                       |
|  | This product complies with the WEEE Directive and its marking requirements. The affixed label indicates that you must not discard this electrical/electronic product in domestic household waste. Do not dispose of this product as unsorted municipal waste. For information about take-back and recycling programs available in your country, see the website. |

## Maintenance

Clean with a soft towel moistened with water and mild detergent.  
DO NOT IMMERSE in liquid.

## Product Disposal

Dispose of the Product in a professional and environmentally appropriate manner:

- Put the Product in the electrical waste.

## Specifications

|                       |                                                                                |
|-----------------------|--------------------------------------------------------------------------------|
| Safety .....          | IEC 61010-031, CAT III 1500 V, 20 A<br>Pollution Degree 2                      |
| Operating and Storage |                                                                                |
| Temperature .....     | -20 °C to 50 °C (-4 °F to 122 °F)                                              |
| Humidity .....        | <95 % RH, up to 35 °C (95 °F)<br><40 % RH, 35 °C to 50 °C<br>(95 °F to 122 °F) |
| Altitude .....        | 2000 m                                                                         |

### LIMITED WARRANTY

This Fluke product will be free from defects in material and workmanship for 1 year from the date of purchase. This warranty does not cover fuses, disposable batteries, or damage from accident, neglect, misuse, alteration, contamination, or abnormal conditions of operation or handling. Resellers are not authorized to extend any other warranty on Fluke's behalf. To obtain service during the warranty period, contact your nearest Fluke authorized service center to obtain return authorization information, then send the product to that Service Center with a description of the problem.

THIS WARRANTY IS YOUR ONLY REMEDY. NO OTHER WARRANTIES, SUCH AS FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSED OR IMPLIED. FLUKE IS NOT LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES OR LOSSES, ARISING FROM ANY CAUSE OR THEORY. Since some states or countries do not allow the exclusion or limitation of an implied warranty or of incidental or consequential damages, this limitation of liability may not apply to you.

11/99